

P r o d u c t



B u l l e t i n

September 2006

www.ektorque.com



RETW

Electronic Torque Wrench



Accuracy +/- 2% of reading, +/- 1 digit

Designed for daily screw tightening production environment.

Program pre-set torque.

Rotating head allows viewing of the display from any angle.

Three units of torque measurement available: N.m, lbf.ft, lbf.in

Selection of two operating modes: Track and Peak.

Heavy duty ratchet head or interchangeable end fittings

Go/No Go LED's and a buzzer can be set for a high or low torque limits.

Four-digit display.

Battery operation (Optional - rechargeable battery adapter kit)

Optional RS-232 serial interface to download torque readings to a PC or printer.

| Model | Item # | Torque Ranges | | Length | | Drive | Weight | |
|-----------|--------|-----------------|------------------|--------|-----|-------------|--------|-----|
| | | American | S.I. | in. | mm | | lbs. | kg. |
| RETW250i | 290106 | 25 - 250 lbf.in | 3 - 30 N.m | 15 | 381 | 3/8 Sq Dr. | 2.2 | 0.9 |
| IRETW250i | 290110 | 25 - 250 lbf.in | 3 - 30 N.m | 15 | 381 | 9x12 End | 2.2 | 0.9 |
| RETW100F | 290107 | 10 - 100 lbf.ft | 13.6 - 135.6 N.m | 17 | 431 | 3/8 Sq Dr. | 2.4 | 1.1 |
| IRETW100F | 290111 | 10 - 100 lbf.ft | 13.6 - 135.6 N.m | 17 | 431 | 14x18 End | 2.4 | 1.1 |
| RETW150F | 290108 | 15 - 150 lbf.ft | 20.3 - 203.3 N.m | 19 | 480 | 1/2" Sq. Dr | 2.8 | 1.3 |
| IRETW150F | 290112 | 15 - 150 lbf.ft | 20.3 - 203.3 N.m | 19 | 480 | 14x18 End | 2.8 | 1.3 |
| RETW250F | 290109 | 25 -250 lbf.ft | 33.9 - 339 N.m | 22 | 550 | 1/2" Sq. Dr | 3 | 1.4 |
| IRETW250F | 290113 | 25 -250 lbf.ft | 33.9 - 339 N.m | 22 | 550 | 14x18 End | 3 | 1.4 |

Accessories

Item # 290114

Model: RS-232 and Rechargeable Battery Adapter Kit

Description: RS-232 serial interface to download torque readings. Battery charger.



NOTE!

Uses standard AA batteries

v 1.0