



Product Bulletin

PB # 0004
May 2007



408.292.2214
408.292.2733
sales@etorque.com
www.etorque.com

STB

Cam-Over Torque Wrench, Internally Preset 16mm Spigot for Interchangeable Heads



Key Features

Designed and manufactured to meet or exceed the accuracy and repeatability requirements of ISO 6789: 2003 (+/- 4% of setting).

A preset production torque wrench.

The wrench “slips” through a 110° break before automatically resetting inline, reducing the possibility of overtorquing.

Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer.

Features the new mechanical torque adjustment locking device (M-TALD). An auto locking single key operation prevents tampering.

Compatible with 16mm spigot Interchangeable Heads (see page 4.6 in Mountz Catalog MC13).

Versatile wrench suitable for most applications.

ESD compliant (IEC 61340-5-1:1998).

Interchangeable Heads



The versatile STB features a 16mm spigot, which allows it to be used with a variety of head options:

1. Open End
2. Box End
3. Flare End
4. Ratchet Drive
5. Blank End

Accessories

Replace the end cap of the STB with a “Loop” end cap for hanging the wrench safely when it’s not being used. Made with anodized aluminum and stainless steel folding loop.



Item # 020485 List Price: \$85.00 Code: D

Model	Item #	Torque Ranges			Length		Drive Size	Weight	
		lbf.ft	N.m	kgf.m	in.	mm		lbs.	kg.
STB35	020158	5.2 - 25	7 - 35	0.7 - 3.5	10	255	16mm Spigot	1.1	0.49